



K-POS

Stunning POS system with high level of performance

- High performance CPU
- Clear and high-quality LED screen
- Low noise and low heat by applying Fan-less method
- Sleek exterior design with soft curve
- Thin and neat exterior
- Assembly/disassembly possible without additional tools
- Easy maintenance and repair



K-9000



Slim & Sleek Style POS System, K-POS

OKPOS' POS terminals are undefeated in innovation and have a solid commitment in providing the optimum combination of performance and value. K-POS is designed to provide outstanding performance for your business and to protect your business. Our POS terminals are designed to accelerate customer service and K-POS shows business-optimized technologies, innovative design.



Product reliability & safety

Proven product reliability and safety through EMC test, KC, CE and FCC by Authorized Testing and Certification Bodies

Green IT

Intel Atom processor offers low power consumption. Low energy consumption can reduce unnecessary heat and expand the life span of POS components.



Slim and perfectly flat



USB port next to power button



Clear high-quality screen with a LED Backlight



Sufficient I/O ports to connect with peripheral equipment

Specifications

Item	Specification		
CPU	Intel 1037U	Intel® Celeron® 1037U (2M Cache, 1.80 GHz)	
Main	Memory	DDR3 SODIMM 2GB (up to 8GB by 2 x Slots)	
	Storage	2.5" SATA- II 320GB HDD & SSD(64GB/128GB)	
Primary Display	LCD	15-inch TFT LCD (250cd), W / LED Back-light, LVDS Interface	
	Resolution	1024 x 768	
	Touch	15-inch 5-wire Resistive , Serial interface	
	Speaker	1 x 1W	
	USB	6 x USB (Rear: 4 x USB, Side: 2 x USB)	
	Serial	4 x RS-232C (3 x Powered DSUB-9, 1 x RJ-45)	
	PS/2	1 x Keyboard or Mouse	
	LAN	1 x Gigabit LAN	
	VGA	1 x RGB	
	Audio	2 ports (1 x Mic-in, 1 x Line-out)	
Power	DC-IN	External 60/72W Adapter	
		Input AC 100~240V/50~60Hz, Output DC 12V/5A or 6A	
User Environment	Temperature	Operating -25 °C to 65 °C, Storage -35 °C to 75 °C	
Size	Dimension	341 x 345 x 209 mm (W x D x H)	
	Weight	6.6kg	
Optional Peripherals	MSR	ISO 1,2,3 Tracks Reading	
	SCR	EMV level 1, 2	
	OS	POSReady2009 / POSReady7	
	2nd Display	15-inch TFT LCD (1024 x 768), W / LED Back-light (Touch or Non-Touch)	
		9.7-inch TFT LCD (1024 x 768), W / LED Back-light (Touch or Non-Touch)	
	CDP	VFD (20 columns x 2 lines)	
	Dallas	Dallas I-button Reader	
	Cash Drawer Port	Serial trigger	
	CPU	Intel® Celeron® J1900 (2M Cache, up to 2.42 GHz)	
		Intel® Core™ i3-3217UE (3M Cache, 1.60 GHz)	
Intel® Core™ i7-3517UE (4M Cache, up to 2.80 GHz)			